



SPECIFICATION:

- 1). Driving: Duty:1/240, Bias:1/16, VDD:5.0V, V0:22.0V(Ref.)
- 2). VIEWING DIRECTION: 6 O'CLOCK
- 3). Display mode: STN/Negative/Transmissive/Blue
- 4). Operating temp.: -20°C~+70°C
- 5). Storage temp.: -30°C~+80°C
- 6). USE IC: NT7701/NT7702
- 7). Backlight: EDGE/CCFL White
- 8). DIMENSIONS WITH MARK "\*" ARE IMPORTANT WITH MARK "()" ARE REFERENCED
- 9). All the raw materials are RoHS compliant

1	2	3	4	5	6	7	8	9	10	11	12
FRM	LP	CP	NC	DISP	D0	D1	D2	D3	VDD	VSS	V0

REV REVISION RECORD

REV	REVISION RECORD	DATE
A0	First issue	12-10



深圳市三元晶液晶显示科技有限公司  
Shenzhen TCC LCD Hi-Tech Co., Ltd.

DRAWING NO.	SYT32019TV16-5BFM7-B6NZE-T04.5	GENERAL TOL:	±0.2
APPROVED BY	CHECKED BY	DRAWING BY	UNIT: mm
			PAGE
			1/1

DOTS DETAIL

